



We specialise in
fire extinguishers for Automotive category

DRY CHEMICAL POWDER TYPE FIRE EXTINGUISHERS
(STORED PRESSURE)

1A MAP (Mono Ammonium Phosphate) based Powder



Fire Fite® ABC stored pressure fire extinguishers contain Mono Ammonium Phosphate based dry powder as per IS 14609.

Also called *multi purpose fire extinguishers*, these are useful for all classes of fire involving materials like oil, fats, gases, solvents, paint, varnish, electrical wiring and live machinery.

Also available with UL approved / MAP 90% powder & safety valve



SPECIFICATION IS 15683 : 2006

CAPACITY	1 KG	2 KGS	4 KGS	6 KGS	9 KGS
THICKNESS	1.6 mm	1.6 mm	1.6 mm	1.6 mm	1.6 mm
DIAMETER	86 mm	108 mm	150 mm	150 mm	175 mm
HEIGHT	325 mm	360 mm	385 mm	520 mm	570 mm

PERFORMANCE

DISCHARGE TIME	9-12sec	9-13sec	13-25sec	15-25sec	15-25sec
DISCHARGE % (MIN)	85	85	85	85	85
JET LENGTH	Actual 6m Req (2 m)	Actual 6m Req (2 m)	Actual 6m Req (2 m)	Actual 7m Req (2 m)	Actual 8m Req (2 m)

FIRE RATINGS	1A 8B C	1A 8B C upwards	2A 21B C	3A 21B C upwards	4A 34B C
--------------	---------	--------------------	----------	---------------------	----------

TEMPERATURE RATING	-30°C to +55°C
--------------------	----------------

All our fire ratings are
higher than the minimum

Higher fire rating
extinguishers can be
provided

These fire extinguishers are pressured with dry N₂. It extinguishes fire by blanketing, displacement of air and decomposition of dry powder effects.

Extremely Easy to Use.

1B SBC (Sodium Bi-carbonate) based Powder



Fire Fite® brand BC stored pressure fire extinguishers contain Sodium Bi-carbonate based dry powder as per IS 4308.

These are useful to fires involving materials like oil, fats, solvents, gases, electrical wiring, paint, varnish and live machinery.

It extinguishes fire by blanketing, displacement of air and decomposition of dry powder effects.



SPECIFICATION IS 15683 : 2006

CAPACITY	1 KG	2 KGS	4 KGS	6 KGS	9 KGS
THICKNESS	1.6 mm	1.6 mm	1.6 mm	1.6 mm	1.6 mm
DIAMETER	86 mm	108 mm	150 mm	150 mm	175 mm
HEIGHT	325 mm	360 mm	385 mm	520 mm	570 mm

PERFORMANCE

DISCHARGE TIME	9-12sec	9-13sec	13-25sec	15-25sec	15-25sec
DISCHARGE % (MIN)	85	85	85	85	85
JET LENGTH	Actual 6m Req (2 m)	Actual 6m Req (2 m)	Actual 6m Req (2 m)	Actual 7m Req (2 m)	Actual 8m Req (2 m)

FIRE RATINGS	8B C	8B C upwards	21B C	21B C upwards	34B C
--------------	------	-----------------	-------	------------------	-------

TEMPERATURE RATING	-30°C to +55°C
--------------------	----------------

All our fire ratings are higher than the minimum

Higher fire rating extinguishers can be provided