



FLASH LIGHT



Sold & Serviced By :



SURE SAFETY (INDIA) PVT. LTD.

Chhani, Vadodara-391 740, Gujarat-INDIA

Phone : 91-265-2760150 / 162, / M : +91-9099087062 / Fax : 91-265-2774824

✉ info@suresafety.com / 🌐 www.suresafety.com

9460

Remote Area Lighting System



9460 Remote Area Lighting System

Using solid-state mounted LED's coupled with a thermally efficient light engine and our 1510 Pelican Protector™ Case, the RALS 9460 gives the user the ultimate maintenance free portable floodlight station to get the job done efficiently, safely and on time. The RALS 9460 houses two of it's light heads and it's multi-stage charger for that total self contained convenience, it is also equipped with a telescopic handle and rugged wheels for ease of transport.

Comes with convenient low battery warning system and waterproof activation switch.

CAUTION: The Pelican Products RALS models 9450, 9460 and 9470 contain sealed lead acid batteries that can generate hydrogen gas when charging. It is imperative that these products are charged, as instructed, with the case lid open to allow any gases to escape as charging with the lid closed poses a significant hazard. Failure to abide by this instruction could result in injury and/or damage to property. Please refer to the warnings provided in the instructions for the unit and on a decal affixed to the inside of the case adjacent to the cavity where the charger unit is packed.

9460 Remote Area Lighting System Configurations

Cat. #	Description
9460	9460 Remote Area Lighting System



9460 Remote Area Lighting System Specifications

Light Source

LED Type	LED Life	Tested Lumen Value
High Flux LED	50000 hrs.	2000 (Low) 4000 (High)

Lamp Heads	Number of LEDs	Beam Spread
2	24 LEDs per head	90°

Brightness Settings
2

Power Source

Battery Type	Battery Burn Time	Battery Charging Time
12v Rechargeable, Sealed	14 hrs. (Low) 7 hrs. (High)	6 hrs. from full discharge

Battery Life	Low Battery Warning	12V Primary Sockets
500 cycles	Intermittent Blinking	2

12V Auxiliary Sockets	Watts	Voltage
	48	12

Dimensions & Weight

Head Length	Head Width	Head Depth
6.5" (16.5 cm)	7.87" (20 cm)	2.56" (6.5 cm)

Width Closed	Length Closed	Height Closed
--------------	---------------	---------------

Sold & Serviced By :



SURE SAFETY (INDIA) PVT. LTD.

Chhani, Vadodara-391 740, Gujarat-INDIA
 Phone : 91-265-2760150 / 162, / M: +91-9099087062 / Fax: 91-265-2774824
 ✉ info@suresafety.com / 🌐 www.suresafety.com

13.81" (35.1 cm)	22" (55.9 cm)	9" (22.9 cm)
Mast Height Extended	Cord Length (Retracted)	Weight
70.87" (179.9 cm)	13.78" (35 cm)	50.71 lbs. (23 kg)

9460 Remote Area Lighting System Approvals

CE	Approved
CE Certificate	Yes
RoHS (Restriction of Hazardous Substances) Compliant	Approved

9460 Remote Area Lighting System Accessories

Cat. #	Description
9437	Extension Cord 118 inches (3m)
9436	12/24V Vehicle Charger
9430T	9430T Tripod Kit

Sold & Serviced By :



SURE SAFETY (INDIA) PVT. LTD.
Chhani, Vadodara-391 740, Gujarat-INDIA
Phone : 91-265-2760150 / 162, / M: +91-9099087062 / Fax : 91-265-2774824
✉ info@suresafety.com / 🌐 www.suresafety.com



FLASH LIGHT



Sold & Serviced By :



SURE SAFETY (INDIA) PVT. LTD.

Chhani, Vadodara-391 740, Gujarat-INDIA

Phone : 91-265-2760150 / 162, / M : +91-9099087062 / Fax : 91-265-2774824

✉ info@suresafety.com / 🌐 www.suresafety.com



9470 Remote Area Lighting System

Using solid-state mounted LED's coupled with a thermally efficient light engine and our [1610 Pelican Protector™ Case](#), the RALS 9470 gives the user the ultimate maintenance free portable floodlight station to get the job done efficiently, safely and on time. The RALS 9470 houses all four of its light heads and its multi-stage charger for that total self contained convenience, it is also equipped with a telescopic handle and rugged wheels for ease of transport.

Comes with convenient low battery warning system and waterproof activation switch.

CAUTION: The Pelican Products RALS models 9450, 9460 and 9470 contain sealed lead acid batteries that can generate hydrogen gas when charging. It is imperative that these products are charged, as instructed, with the case lid open to allow any gases to escape as charging with the lid closed poses a significant hazard. Failure to abide by this instruction could result in injury and/or damage to property. Please refer to the warnings provided in the instructions for the unit and on a decal affixed to the inside of the case adjacent to the cavity where the charger unit is packed.

9470 Remote Area Lighting System Configurations

Cat. #	Description
9470	9470 Remote Area Lighting System



9470 Remote Area Lighting System Specifications

Light Source

LED Type	LED Life	Tested Lumen Value
High Flux LED	50000 hrs.	4000 (Low) 8000 (High)

Lamp Heads	Number of LEDs	Beam Spread
4	24 LEDs per head	90°

Brightness Settings

2

Power Source

Battery Type	Battery Burn Time	Battery Charging Time
12v Rechargeable, Sealed	14 hrs. (Low) 7 hrs. (High)	8 hrs. from full discharge

Battery Life	Low Battery Warning	12V Primary Sockets
500 cycles	Intermittent Blinking	4

12V Auxiliary Sockets	Watts	Voltage
1	96	12

Dimensions & Weight

Head Length	Head Width	Head Depth
6.5" (16.5 cm)	7.87" (20 cm)	2.56" (6.5 cm)

Width Closed	Length Closed	Height Closed
--------------	---------------	---------------

Sold & Serviced By :



SURE SAFETY (INDIA) PVT. LTD.

Chhani, Vadodara-391 740, Gujarat-INDIA

Phone : 91-265-2760150 / 162, / M: +91-9099087062 / Fax : 91-265-2774824

✉ info@suresafety.com / 🌐 www.suresafety.com

19.57" (49.7 cm)

24.83" (63 cm)

11.93" (30.3 cm)

Mast Height Extended

72.85" (185 cm)

Cord Length (Retracted)

13.78" (35 cm)

Weight

88.18 lbs. (40 kg)

9470 Remote Area Lighting System Approvals



Approved

CE Certificate

Yes

RoHS (Restriction of Hazardous Substances) Compliant

Approved

9470 Remote Area Lighting System Accessories

Cat. #	Description
9437	Extension Cord 118 inches (3m)
9430T	9430T Tripod Kit

Sold & Serviced By :



SURE SAFETY (INDIA) PVT. LTD.

Chhani, Vadodara-391 740, Gujarat-INDIA

Phone : 91-265-2760150 / 162, / M: +91-9099087062 / Fax : 91-265-2774824

✉ info@suresafety.com / 🌐 www.suresafety.com



2755 Headlamp

Pelican™ safety approved headlamps are designed for use in hazardous environments. It is not only Class I Div 1 approved but also is ultra compact and lightweight. Equipped with a single high-powered LED, it produces up to 118 lumens and provides up to 16 hours of run time and offers multiple modes (high, low, flashing). Additionally, the Pelican 2755 offers a low battery indicator which can prove to be most valuable. It is available in two colors (yellow or black). Count on Pelican to bring you the best in lighting design and technology.

The new Pelican™ 2755 headlamp: Guiding you safely through the danger zone.

- Built Pelican tough
- Hands-free design
- Comfortable Cloth Strap
- Safety Certified - Class I, Division I

DIMENSIONS

Length	2.25" (5.7 cm)
--------	----------------

MATERIALS

Body	Polycarbonate (PC)
O-Ring	Over-molded TPR
Lens	Polycarbonate (PC)
Shroud	Polycarbonate (PC)

COLORS

Black	High Visibility Yellow
-------	------------------------

LIGHT SPECS

Lamp Type	LED
-----------	-----

POWER

Battery Size	AAA
Battery Type	Alkaline
Battery Quantity	3
Batteries Included	yes
Battery Level Indicator	Low battery warning
Volts	4.5v

WEIGHT

Weight With Batteries	3.4 oz (96 gr)
Weight Without Batteries	2.1 oz (60 gr)

SWITCH

Switch Type	Push Button
Light Modes	High / Low / Flashing

CERTIFICATIONS

Class I, Division 1 IECEx ia



OTHER

Minimum Pack

FL1 STANDARD	HIGH	LOW
	118 LUMENS	60 LUMENS
	7h 30mins	16h 0mins
	60m	43m
	910cd	454cd
	IP54	

ACCESSORIES



2748
Strapless Headlamp Adapter



3315 Flashlight

COMPACT LED POWER

High Performance LED without the Sticker Shock

The new 3315 LED flashlight: the lightweight compact design houses 3AA batteries that power a single LED for 160 lumens of super bright LED light. Safety approved for the most volatile work environments, the 3315 LED flashlight is one of the most efficient flashlights on the market today. The new 3315 LED flashlight: Compact flashlight, huge LED performance.

- 3 AA Batteries (Included)
- Built Pelican tough
- Class I, Class II, Class III – Division 1 Safety Certified
- Safety Certified Class I, Division 1 / IECEx ia
- Lanyard (included)
- IP67 waterproof and dustproof
- Removable clip included


DIMENSIONS

Length	6.14" (15.6 cm)
--------	-----------------

MATERIALS

Body	High Impact ABS
O-Ring	EPDM
Lens	Polycarbonate (PC)
Clip	Nylon

COLORS

 High Visibility Yellow

LIGHT SPECS

Lamp Type	LED
-----------	-----

POWER

Battery Size	AA
Battery Type	Alkaline
Battery Quantity	3
Batteries Included	yes
Volts	4.5v

WEIGHT

Weight With Batteries	6.2 oz (176 gr)
Weight Without Batteries	3.7 oz (105 gr)

SWITCH






Switch Type	Push Button
-------------	-------------

Light Modes	On / Off
-------------	----------



OTHER

Minimum Pack	1
Package Code	C

FL1 STANDARD	HIGH
	160 LUMENS
	19h 0mins
	144m
	5153cd
	IP67

CERTIFICATIONS

Class I, Division 1
Class II, Division 1
Class III, Division 1
IECEx ia



3315 R-RA Flashlight

Ultra compact, special designed lithium rechargeable and safety certified right angle make the Pelican™ 3315R-RA one of the most versatile work lights available today. Its compact and right angle design is perfect for any hands free applications. The articulating head allows for the light to be used as a conventional handheld light in addition to having the ability to direct the light exactly where you need it. The 3315R-RA produces up to 132 lumens and provides up to 34 hours of continuous run time. 3 modes are provided, High / Low / Flashing. There is a full time battery level indicator built into the power switch so you'll always know when it's time to recharge.

- IPX7 Waterproof
- Full Time Battery Level Indication
- 3 modes High / Strobe / Low
- Safety Certified Class I, Division 1 / IECEx ia
- Lanyard (included)
- Special Lithium rechargeable battery provides 2,000 cycles (a 300% increase)
- Up to 132 Lumens
- Up to 34 hours, 15 minutes run time
- Articulating right angle adapter with clip (included)

DIMENSIONS

Length	7.00" (17.8 cm)
--------	-----------------

MATERIALS

Body	Anti-static Impact Modified PC/PBT
O-Ring	EPDM
Lens	Anti-static coated Polycarbonate (PC)
Shroud	Anti-static Impact Modified PC/PBT
Clip	Stainless Steel

COLORS

	High Visibility Yellow
--	------------------------

LIGHT SPECS

Lamp Type	LED
-----------	-----

POWER

Battery Size	18650
Battery Type	Lithium Iron Phosphate
Battery Quantity	1
Batteries Included	yes
Rechargeable	yes
Charge Time	10 hrs
Battery Level Indicator	RGB LED
Volts	3.2v

WEIGHT

Weight With Batteries	7.1 oz (201 gr)
Weight Without Batteries	5.5 oz (156 gr)

SWITCH

Switch Type	Push Button
Light Modes	High / Low / Flashing

CERTIFICATIONS

Class I, Division 1 IECEx ia



OTHER

Minimum Pack	1
Package Code	C

FL1 STANDARD	HIGH	LOW
	132 LUMENS	15 LUMENS
	5h 0mins	34h 0mins
	108m	35m
	2931cd	308cd
	IP67	



9410L

Less than 3lbs + 2207 lumens = brightest & lightest in its class
At less than 3 pounds and 2207 lumens, the new 9410L LED Lantern packs the power without the weight. Four LEDs, powered by the latest generation Lithium-Ion batteries illuminate a distance of 495 yards (453 meters). And it's loaded with innovative technology and features you have come to expect from Pelican. The 9410L LED Lantern is one of the most compact, high output lanterns on the market.

- Built Pelican tough
- Handy push button on/off switch
- High/Low/Flashing Modes
- Super bright LED beam
- Approved to NFPA (National Fire Protection Association) 1901
- Carrying Strap included



DIMENSIONS

Length	8.75" (22.2 cm)
---------------	-----------------

MATERIALS

Body	ABS
O-Ring	EPDM
Lens	Polycarbonate (PC)
Shroud	EXL

COLORS

 Black	 High Visibility Yellow
---	--

LIGHT SPECS

Lamp Type	LED
------------------	-----

POWER

Battery Size	18650
Battery Type	Lithium-Ion
Battery Quantity	6
Batteries Included	yes
Rechargeable	yes
Charge Time	8 hrs
Battery Level Indicator	RGB LED
Volts	7.2v

WEIGHT







Weight With Batteries	44.7 oz (1267 gr)
Weight Without Batteries	0.0 oz (0 gr)

SWITCH






Switch Type	Push Button
Light Modes	High / Low / Flashing

OTHER

Minimum Pack	1
Package Code	B

FL1 STANDARD	HIGH	LOW
	2207 LUMENS	463 LUMENS
	3h 15mins	11h 0mins
	453m	207m
	51304cd	10710cd
	1m	
	IPX4	

ACCESSORIES

				
8056F 12v Plug-in for Fast Charger	6057F 110V Transformer (USA)	9419L Replacement Battery	9416L Deck/Dash Charger Base Unit	6061F Direct Wiring Rig for Fast Charger

Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311
sales@pelican.com • www.pelican.com

Document created on 12-06-20



FLASH LIGHT



Sold & Serviced By :



SURE SAFETY (INDIA) PVT. LTD.

Chhani, Vadodara-391 740, Gujarat-INDIA

Phone : 91-265-2760150 / 162, / M : +91-9099087062 / Fax : 91-265-2774824

✉ info@suresafety.com / 🌐 www.suresafety.com

LIGHTS

9430

Remote Area Lighting System



Black



Yellow

9430 Remote Area Lighting System

- Up to 15 hours of burntime
- 2000 lumens of brightness
- Maintenance Free LED Array with life expectancy of 50,000 hours
- Fully extendable mast with 360 degree rotating head
- Low Battery Warning System
- Waterproof Rubber Activation Switch
- Mast Extension Lock

NSN #6230-01-569-9643

9430 Remote Area Lighting System Configurations

Cat. #	Description
9430	9430 Remote Area Lighting System

9430 Remote Area Lighting System Specifications

Light Source

LED Type	LED Life	Tested Lumen Value
High Flux LED	50000 hrs.	1000 (Low) 2000 (High)

Lamp Heads	Number of LEDs	Beam Spread
1	24 LEDs per head	90°

Brightness Settings

2

Power Source

Battery Type	Battery Burn Time	Battery Charging Time
12v Rechargeable, Sealed	15 hrs. (Low) 8 hrs. (High)	5 hrs. from full discharge

Battery Life	Low Battery Warning	12V Primary Sockets
500 cycles	Intermittent Blinking	1

12V Auxiliary Sockets	Watts	Voltage
1	24	12


Dimensions & Weight

Head Length	Head Width	Head Depth
6.5" (16.5 cm)	7.87" (20 cm)	2.56" (6.5 cm)

Width Closed	Length Closed	Height Closed
7.87" (20 cm)	15.75" (40 cm)	9.06" (23 cm)

Mast Height Extended	Cord Length (Retracted)	Weight
32.28" (82 cm)	13.78" (35 cm)	22.65 lbs. (10.27 kg)

9430 Remote Area Lighting System Approvals

 PDFmyURL.com

Sold & Serviced By :



SURE SAFETY (INDIA) PVT. LTD.

Chhani, Vadodara-391 740, Gujarat-INDIA

Phone : 91-265-2760150 / 162, / M: +91-9099087062 / Fax : 91-265-2774824

✉ info@suresafety.com / 🌐 www.suresafety.com



Approved

CE Certificate

Yes

RoHS (Restriction of Hazardous Substances) Compliant

Approved

9430 Remote Area Lighting System Accessories

Cat. #	Description
1460AALG	1460 Case (with custom foam for 9430/9435)
9438	9430 RALS Universal Charger
9437	Extension Cord 118 inches (3m)
9436	12/24V Vehicle Charger
9434	Spare LED Head including Mast
9432	9430 Back Pack
9431	9430 Tear-Off Back Pack
9430T	9430T Tripod Kit

Pelican Products, Inc.

23215 Early Avenue • Torrance, CA 90505 • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311
e-mail: sales@pelican.com • www.pelican.com

Sold & Serviced By :**SURE SAFETY (INDIA) PVT. LTD.**

Chhani, Vadodara-391 740, Gujarat-INDIA

Phone : 91-265-2760150 / 162, / M: +91-9099087062 / Fax : 91-265-2774824

✉ info@suresafety.com / 🌐 www.suresafety.com